

▼ AUSWAHLTABELLE

Geeignet für Zylinderkapazität	Druckstücke			Zylinderfuß	Flanschbefestigung	Einhängeösen	
	Flach	Gerillt ¹⁾	Beweglich			Fuß ⁴⁾	Kolben
t (kN)							
5 (45)	A-53F ²⁾	A-53G ²⁾	–	–	RB-5 ²⁾ , AW-51 ²⁾ , AW-53 ²⁾	REB-5 ²⁾	REP-5 ²⁾
10 (101)	A-12 ³⁾ , A-102F ³⁾	A-102G ³⁾	CAT-10 ³⁾	JB1-10 ³⁾	RB-10, AW-102	REB-10	REP-10 ³⁾
15 (142)	–	A-152G	CAT-10	–	RB-15	REB-15	REP-10
25 (232)	A-29 ⁵⁾	A-252G	CAT-50	JB1-25	RB-25	REB-25	REP-25
30 (295)	A-29 ⁵⁾	A-252G	CAT-50	–	RB-25	–	REP-25
50 (498)	–	–	CAT-100	JB1-50	–	–	–
75 (718)	–	–	CAT-100	–	–	–	–
95 (933)	–	–	CAT-100	–	–	–	–

¹⁾ Standard bei 5-30 t RC-Zylinder ²⁾ Außer RC-50 ³⁾ Außer RC-101 ⁴⁾ Montageschrauben werden mitgeliefert. ⁵⁾ Für Rohrbieger

▼ MASSTABELLE

Modellnr.	Abmessungen der Druckstücke (mm)			A-53F, A-102F	A-12, A-29
	A	B	C		
	Flach				
A-53F	25	6	17		
A-102F	35	6	22		
A-12	51	48	1" - 8 UNC		
A-29	51	48	1½" - 16 UNC		
	Gerillt				
A-53G	25	6	17		
A-102G	35	6	22		
A-152G	38	9	22		
A-252G	50	9	35		

Modellnr.	Abmessungen der Zylinderfüße (mm)				
	A	B	C	D	E
JB1-10	228	228	135	58	20
JB1-25	279	279	140	86	26
JB1-50	304	15	95	131	31

Modellnr.	Abmessungen der Flanschbefestigungen (mm)							
	A	B	C	D	E	F	G	H
RB-5	1½" - 16UN	88	76	–	25	–	–	–
AW-51	1½" - 16UN	70	59	10	24	54	¼" - 16 UN	41
AW-53	1½" - 16UN	72	7	7	19	57	¼" - 20 UN	10
RB-10	2¼" - 14UN	114	88	–	25	–	–	–
AW-102	2¼" - 14UN	100	82	16	30	76	7/16" - 20 UN	58
RB-15	2¾" - 16UN	101	114	–	38	–	–	–
RB-25	3½" - 12UN	127	165	–	50	–	–	–

Typ	Modellnr.	Abmessungen der Eihängeösen (mm)						Stichmaß* (mm)
		A	B	C	D	E	F	
Fuß ⁴⁾	REB-5	44	47	14	16	16	25	60,2
	REB-10	63	66	25	22	25	35	78,0
	REB-15	76	66	25	22	25	35	78,0
	REB-25	95	79	38	31	31	41	87,6
Kolben	REP-5	28	45	14	16	16	19	–
	REP-10	42	61	25	22	25	28	–
	REP-25	57	71	38	31	31	35	–

⁴⁾ Montageschrauben werden mitgeliefert.

* Stichmaß – mit REB- und REP-Schwenkauge. Zylinderbauhöhe eingefahren addieren.